

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

AC 20A / 220V FIC (F) Power Plug (Push-Pull_4SQ)

유비씨에스의 DC/AC 전원 커넥터는 4G & 5G 무선 장비, 정류기 등 옥외 무선네트워크 환경에서 기지국과 장비를 상호연결하며, 전원을 공급하는 데 주로 사용됩니다.

FEATURES / BENEFITS

- 1 Safety & Easy field installation
- 2 Compatible with rectifier equipment
- 3 Safety waterproofing function
- 4 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions



FIC : Field Installable Connector

SAC : Solder Assembled Connector

SS : Samsung

NK : Nokia

ELG : Ericsson

M : Male

F : Female

RC : Rectifier

PP : Push-Pull Type

BN : Bayonet Type

SC : Screw Type

FUNCTIONAL SPECIFICATIONS

Connector Type	Push-Pull / FIC / Female
Connector Dimension	Ø32 x 98mm
Dust & Waterproof Rate	IP67 ~ IP68
Mating Durability	500 (Cycle)
Pulling Force	200N

OPERATING SPECIFICATIONS

Rated Voltage	AC 220V
Rated Current	20A
Dielectric Withstanding Voltage	AC 1000V, 5mA, 60sec
Insulation Resistance	DC 500V, 10sec, Min 100MΩ
Contact Resistance	≤1.25mΩ

ENVIRONMENT TEST

Air-Leakage	1bar / 30second (Less than 0.03bar)
Operating Temperature	-40 to +85°C
UV Test	720hours
Corrosion Test	Temperature: 35°C / Salinity 5% / Spray volume 1~2 ml / Test time: 168 hrs (KSD 9502)
Vibration Test	Vibration frequency: 10~55Hz, displacement: 0.75mm, time of duration: 6H

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

AC 20A / 220V SAC (M) Power Receptacle (Push-Pull)

유비씨에스의 DC/AC 전원 커넥터는 4G & 5G 무선 장비, 정류기 등 옥외 무선네트워크 환경에서 기지국과 장비를 상호연결하며, 전원을 공급하는 데 주로 사용됩니다.

FEATURES / BENEFITS

- 1 Safety & Easy field installation
- 2 Compatible with rectifier equipment
- 3 Safety waterproofing function
- 4 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions



FIC : Field Installable Connector
 SAC : Solder Assembled Connector
 SS : Samsung
 NK : Nokia
 ELG : Ericsson
 M : Male

F : Female
 RC : Rectifier
 PP : Push-Pull Type
 BN : Bayonet Type
 SC : Screw Type

FUNCTIONAL SPECIFICATIONS

Connector Type	Push-Pull / Male
Connector Dimension	32.6 x 32.6 x 41.2mm
Dust & Waterproof Rate	IP68
Mating Durability	300 (Cycle)

OPERATING SPECIFICATIONS

Rated Voltage	AC 220V
Rated Current	20A
Dielectric Withstanding Voltage	AC 1000V

ENVIRONMENT TEST

Operating Temperature	-40 to +90°C
-----------------------	--------------

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

DC 40A / 50V SAC (F) Power Receptacle (Push-Pull)

유비씨에스의 DC/AC 전원 커넥터는 4G & 5G 무선 장비, 정류기 등 옥외 무선네트워크 환경에서 기지국과 장비를 상호연결하며, 전원을 공급하는 데 주로 사용됩니다.

FEATURES / BENEFITS

- 1 Safety & Easy field installation
- 2 Compatible with rectifier equipment
- 3 Safety waterproofing function
- 4 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions



FIC : Field Installable Connector
 SAC : Solder Assembled Connector
 SS : Samsung
 NK : Nokia
 ELG : Ericsson
 M : Male

F : Female
 RC : Rectifier
 PP : Push-Pull Type
 BN : Bayonet Type
 SC : Screw Type

FUNCTIONAL SPECIFICATIONS

Connector Type	Push-Pull / Female
Connector Dimension	32.6 x 32.6 x 41.2mm
Dust & Waterproof Rate	IP68
Mating Durability	300 (Cycle)

OPERATING SPECIFICATIONS

Rated Voltage	DC 200V
Rated Current	40A
Dielectric Withstanding Voltage	AC 1000V

ENVIRONMENT TEST

Operating Temperature	-40 to +90°C
-----------------------	--------------

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

DC 40A / 50V SAC & FIC (M) Power Plug (Push-Pull_4SQ)

유비씨에스의 DC/AC 전원 커넥터는 4G & 5G 무선 장비, 정류기 등 옥외 무선네트워크 환경에서 기지국과 장비를 상호연결하며, 전원을 공급하는 데 주로 사용됩니다.

FEATURES / BENEFITS

- 1 Compatible with rectifier equipment
- 2 Safety waterproofing function
- 3 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions



FIC : Field Installable Connector
 SAC : Solder Assembled Connector
 SS : Samsung
 NK : Nokia
 ELG : Ericsson
 M : Male

F : Female
 RC : Rectifier
 PP : Push-Pull Type
 BN : Bayonet Type
 SC : Screw Type

FUNCTIONAL SPECIFICATIONS

Connector Type	Push-Pull / SOC & FIC / Male
Connector Dimension	Ø32 x 79mm (SOC) / Ø32 x 98mm (FIC)
Dust & Waterproof Rate	IP67 ~ IP68
Mating Durability	500 (Cycle)
Pulling Force	200N

OPERATING SPECIFICATIONS

Rated Voltage	DC 48V
Rated Current	40A
Dielectric Withstanding Voltage	AC 1000V, 5mA, 60sec
Insulation Resistance	DC 500V, 10sec, Min 100MΩ
Contact Resistance	≤1.25mΩ

ENVIRONMENT TEST

Air-Leakage	1bar / 30second (Less than 0.03bar)
Operating Temperature	-40 to +85°C
UV Test	720hours
Corrosion Test	Temperature: 35°C / Salinity 5% / Spray volume 1~2 ml / Test time: 168 hrs (KSD 9502)
Vibration Test	Vibration frequency: 10~55Hz, displacement: 0.75mm, time of duration: 6H

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

DC 40A / 50V SAC (M) Power Plug (Push-Pull_4SQ)

유비씨에스의 DC/AC 전원 커넥터는 4G & 5G 무선 장비, 정류기 등 옥외 무선네트워크 환경에서 기지국과 장비를 상호연결하며, 전원을 공급하는 데 주로 사용됩니다.

FEATURES / BENEFITS

- 1 Compatible with high power outdoor equipment for 5G antenna etc.
- 2 Safety waterproofing & Dust protect function
- 3 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions



FIC : Field Installable Connector

SAC : Solder Assembled Connector

SS : Samsung

NK : Nokia

ELG : Ericsson

M : Male

F : Female

RC : Rectifier

PP : Push-Pull Type

BN : Bayonet Type

SC : Screw Type

FUNCTIONAL SPECIFICATIONS

Connector Type	Push-Pull / SOC / Male
Connector Dimension	Ø32 x 83mm
Dust & Waterproof Rate	IP67 ~ IP68
Mating Durability	500 (Cycle)
Pulling Force	200N

OPERATING SPECIFICATIONS

Rated Voltage	DC 48V
Rated Current	40A to 63A
Dielectric Withstanding Voltage	AC 1000V, 5mA, 60sec
Insulation Resistance	DC 500V, 10sec, Min 100MΩ
Contact Resistance	≤1.25mΩ

ENVIRONMENT TEST

Air-Leakage	1bar / 3second (Less than 0.03bar)
Operating Temperature	-40 to +85℃
UV Test	720hours
Corrosion Test	Temperature: 35℃ / Salinity 5% / Spray volume 1~2 ml / Test time: 720hrs
Vibration Test	Vibration frequency: 10~55Hz, displacement: 0.75mm, time of duration: 6hrs

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

DC 40A / 50V FIC (F) Power Plug (Push-Pull_4SQ)

유비씨에스의 DC/AC 전원 커넥터는 4G & 5G 무선 장비, 정류기 등 옥외 무선네트워크 환경에서 기지국과 장비를 상호연결하며, 전원을 공급하는 데 주로 사용됩니다.

FEATURES / BENEFITS

- 1 Safety & Easy field installation cables
- 2 Compatible with outdoor equipment for 5G antenna etc.
- 3 Safety waterproofing & Dust protect function
- 4 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions

FIC : Field Installable Connector
 SAC : Solder Assembled Connector
 SS : Samsung
 NK : Nokia
 ELG : Ericsson
 M : Male

F : Female
 RC : Rectifier
 PP : Push-Pull Type
 BN : Bayonet Type
 SC : Screw Type



FUNCTIONAL SPECIFICATIONS

Connector Type	Push-Pull / FIC / Female
Connector Dimension	Ø32 x 98mm
Dust & Waterproof Rate	IP67 ~ IP68
Mating Durability	500 (Cycle)
Pulling Force	200N

OPERATING SPECIFICATIONS

Rated Voltage	DC 48V
Rated Current	40A
Dielectric Withstanding Voltage	AC 1000V, 5mA, 60sec
Insulation Resistance	DC 500V, 10sec, Min 100MΩ
Contact Resistance	≤1.25mΩ

ENVIRONMENT TEST

Air-Leakage	1bar / 1minute (Less than 0.03bar)
Operating Temperature	-40 to +85°C
UV Test	720hours
Corrosion Test	Temperature: 35°C / Salinity 5% / Spray volume 1~2 ml / Test time: 720 hrs
Vibration Test	Vibration frequency: 10~55Hz, displacement: 0.75mm, time of duration: 6H

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

DC 65A / 50V FIC (F) Power Plug (Push-Pull_6SQ)

유비씨에스의 DC/AC 전원 커넥터는 4G & 5G 무선 장비, 정류기 등 옥외 무선네트워크 환경에서 기지국과 장비를 상호연결하며, 전원을 공급하는 데 주로 사용됩니다.

FEATURES / BENEFITS

- 1 Safety & Easy field installation cables
- 2 Compatible with High power outdoor equipment for 5G antenna etc.
- 3 Safety waterproofing & Dust protect function
- 4 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions



FIC : Field Installable Connector
 SAC : Solder Assembled Connector
 SS : Samsung
 NK : Nokia
 ELG : Ericsson
 M : Male

F : Female
 RC : Rectifier
 PP : Push-Pull Type
 BN : Bayonet Type
 SC : Screw Type

FUNCTIONAL SPECIFICATIONS

Connector Type	Push-Pull / FIC / Female
Connector Dimension	Ø32 x 98mm
Dust & Waterproof Rate	IP67 ~ IP68
Mating Durability	500 (Cycle)
Pulling Force	200N

OPERATING SPECIFICATIONS

Rated Voltage	DC 48V
Rated Current	63A
Dielectric Withstanding Voltage	AC 1000V, 5mA, 60sec
Insulation Resistance	DC 500V, 10sec, Min 100MΩ
Contact Resistance	≤1.25mΩ

ENVIRONMENT TEST

Air-Leakage	1bar / 3sec (Less than 0.03bar)
Operating Temperature	-40 to +85°C
UV Test	720hours
Corrosion Test	Temperature: 35°C / Salinity 5% / Spray volume 1~2 ml / Test time: 720 hrs
Vibration Test	Vibration frequency: 10~55Hz, displacement: 0.75mm, time of duration: 6H

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

Signal 5A Connector & Cable Assembly (Push-Pull)

유비씨에스의 Signal 커넥터 및 케이블 어셈블리는 옥외 무선네트워크 환경에서 사용자의 편의를 위해 설계 되었으며, 최고의 연결 솔루션을 제공 합니다.

FEATURES / BENEFITS

- 1 Push-Pull Type for easy field installation
- 2 Compatible with rectifier equipment
- 3 Excellent durability
- 4 High and Safety communication signal performance
- 5 Complied of IP67 & IP68 outdoor level

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions

FIC : Field Installable Connector
SAC : Solder Assembled Connector
SS : Samsung
NK : Nokia
ELG : Ericsson
M : Male

F : Female
RC : Rectifier
PP : Push-Pull Type
BN : Bayonet Type
SC : Screw Type



SPECIFICATIONS

SPECIFICATIONS	
Connector Type	Push-Pull
Mating Cycle	300 (Cycle)
Rated Voltage	50V
Rated Current	5A
Withstanding Voltage	1000V
Insulation Resistance	DC 500V, 10sec, Min 100MΩ
Operating Temperature	-40 to +90°C
Waterproof	IP67 ~ IP68

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

DC 80A / 50V SAC (F) Power Receptacle (Push-Pull)

유비씨에스의 DC/AC 전원 커넥터는 4G & 5G 무선 장비, 정류기 등 옥외 무선네트워크 환경에서 기지국과 장비를 상호연결하며, 전원을 공급하는 데 주로 사용 됩니다.

FEATURES / BENEFITS

- 1 Safety & Easy connection mount [Push-Pull Type]
- 2 Compatible all of rectifier & batteries for high power equipment
- 3 Safety waterproofing function
- 4 Easy & Safety solder type

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions



FIC : Field Installable Connector
 SAC : Solder Assembled Connector
 SS : Samsung
 NK : Nokia
 ELG : Ericsson
 M : Male

F : Female
 RC : Rectifier
 PP : Push-Pull Type
 BN : Bayonet Type
 SC : Screw Type

FUNCTIONAL SPECIFICATIONS

Connector Type	Push-Pull / Female
Connector Dimension	Ø33 x 37.6mm
Dust & Waterproof Rate	IP67 ~ IP68
Mating Durability	300 (Cycle)

OPERATING SPECIFICATIONS

Rated Voltage	DC 420V
Rated Current	80A
Dielectric Withstanding Voltage	2000V

ENVIRONMENT TEST

Operating Temperature	-40 to +85°C
-----------------------	--------------

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

DC 80A / 50V Cable Assembly (Push-Pull)

유비씨에스의 DC/AC 전원 케이블 어셈블리는 4G & 5G 무선 장비, 정류기 등 옥외 무선네트워크 환경에서 기지국과 장비를 상호 연결하며, 전원을 공급하는 데 주로 사용됩니다.

FEATURES / BENEFITS

- 1 Safety & Easy field installation [Push-Pull Type]
- 2 Compatible between rectifier & battery equipment
- 3 Safety waterproofing function
- 4 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions



FIC : Field Installable Connector
 SAC : Solder Assembled Connector
 SS : Samsung
 NK : Nokia
 ELG : Ericsson
 M : Male

F : Female
 RC : Rectifier
 PP : Push-Pull Type
 BN : Bayonet Type
 SC : Screw Type

FUNCTIONAL SPECIFICATIONS

Connector Type	Push-Pull / Male
Dust & Waterproof Rate	IP67 ~ IP68
Mating Durability	300 (Cycle)

OPERATING SPECIFICATIONS

Rated Voltage	DC 420V
Rated Current	80A
Dielectric Withstanding Voltage	2000V
Insulation Resistance	DC 500V, 10sec, Min 100MΩ

ENVIRONMENT TEST

Operating Temperature	-40 to +85°C
-----------------------	--------------

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Power, Optic Connectors & Cable Assemblies

CPRI DLC (6.3mm) Optic Plug (Push-Pull)

유비씨에스의 Optic 케이블 어셈블리는 옥외 무선네트워크 환경에서 사용자의 편의를 위해 설계 되었으며, 최고의 연결 솔루션을 제공 합니다.

FEATURES / BENEFITS

- 1 Push-Pull Type for easy field installation
- 2 Moving tolerance length for SFP position of inner equipment
- 3 High and Safety optical performance
- 4 Complied of IP67 & IP68 outdoor level
- 5 Satisfy CPRI communication conditions

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions

FIC : Field Installable Connector
 SAC : Solder Assembled Connector
 SS : Samsung
 NK : Nokia
 ELG : Ericsson
 M : Male

F : Female
 RC : Rectifier
 PP : Push-Pull Type
 BN : Bayonet Type
 SC : Screw Type



SPECIFICATIONS

SPECIFICATIONS	
Connector Type	Push-Pull
Operating Wavelength	1260 ~ 1620nm
Environmental Conditions	Outdoor
Configuration	Single Mode (9/125μm)
Insertion Loss	≤0.5dB
Return Loss	≥50dB
Operating Temperature	-40 to +85°C
Storage Temperature	-40 to +85°C
Waterproof	IP67 ~ IP68
UV & Salt Spray Test	720hours

OJC Waterproof Kit (Screw_SS / NK / ELG)

유비씨에스의 방수키트는 혹독한 옥외 환경에서 커넥터를 습기와 먼지 발생에서 보호합니다. 무선 네트워크 영역에서 주로 FTTA와 같은 솔루션 장비 간 연결에 사용됩니다.

FEATURES / BENEFITS

- 1 Safety & Easy field installation [Screw Type]
- 2 Compatible with RRU or AAU equipment
- 3 Safety waterproofing function
- 4 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions

FIC : Field Installable Connector
 SAC : Solder Assembled Connector
 SS : Samsung
 NK : Nokia
 ELG : Ericsson
 M : Male

F : Female
 RC : Rectifier
 PP : Push-Pull Type
 BN : Bayonet Type
 SC : Screw Type



SPECIFICATIONS

SPECIFICATIONS	
Connector Type	Screw Type
Waterproof Rate	IP64
Mating Durability	500 (Cycle)
Temperature Rating	-40 to +85°C

Power, Optical Fiber Connectivity - Outdoor Wireless Networks

Accessories (Waterproof Kits)

RJ45 Alarm Waterproof Kit (Screw_SS)

유비씨에스의 방수키트는 혹독한 옥외 환경에서 커넥터를 습기와 먼지 발생에서 보호합니다. 무선 네트워크 영역에서 주로 FTTA와 같은 솔루션 장비 간 연결에 사용됩니다.

FEATURES / BENEFITS

- 1 Safety & Easy field installation [Screw Type]
- 2 Compatible with rectifier equipment
- 3 Safety waterproofing function
- 4 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions

FIC : Field Installable Connector
 SAC : Solder Assembled Connector
 SS : Samsung
 NK : Nokia
 ELG : Ericsson
 M : Male

F : Female
 RC : Rectifier
 PP : Push-Pull Type
 BN : Bayonet Type
 SC : Screw Type



SPECIFICATIONS

SPECIFICATIONS	
Connector Type	Screw Type
Waterproof Rate	IP64
Mating Durability	500 (Cycle)
Temperature Rating	-40 to +85°C

RJ45 Waterproof Kit (Screw_Rectifier)

유비씨에스의 방수키트는 혹독한 옥외 환경에서 커넥터를 습기와 먼지 발생에서 보호합니다. 무선 네트워크 영역에서 주로 FTTA와 같은 솔루션 장비 간 연결에 사용됩니다.

FEATURES / BENEFITS

- 1 Safety & Easy field installation
- 2 Compatible with rectifier equipment
- 3 Safety waterproofing function
- 4 Excellent durability

APPLICATIONS

- 1 5G Networks
- 2 Outdoor Wireless Networks
- 3 FTTA Solutions

FIC : Field Installable Connector
SAC : Solder Assembled Connector
SS : Samsung
NK : Nokia
ELG : Ericsson
M : Male

F : Female
RC : Rectifier
PP : Push-Pull Type
BN : Bayonet Type
SC : Screw Type



SPECIFICATIONS

Connector Type	Screw Type
Waterproof Rate	IP67
Mating Durability	300 (Cycle)
Temperature Rating	-40 to +85°C